

Flange Type Immersion Heaters



APPLICATION

Flanged immersion heaters are one of the most widely used methods for heating gases and liquids (such as water, oil, heat transfer fluid and corrosive solutions). Designed for use in tanks and pressurized vessels, they are easy to install and maintain to provide heat for many processes. The direct immersion method is energy efficient and easily monitored and controlled.

- Hot Water Storage Tanks
- Warming Equipment
- Preheating All Grades of Oil
- Food Processing Equipment
- Cleaning and Rinsing Tanks
- Heat Transfer Systems
- Process Air Equipment
- Boiler Equipment
- Freeze Protection of Any Fluid



Heaters with Flameproof Terminal Cover

CONSTRUCTION

Flanged Immersion Heaters consist of bent tubular elements welded or brazed into a flange and provided with wiring boxes for electrical connections. Flange heaters are installed by bolting to a matching flange welded to the tank wall or nozzle. A wide selection of flange sizes, kilowatt ratings, voltages, terminal enclosures and sheath materials make these heaters ideal for all types of heating applications.

STANDARD SIZES & CAPACITIES

Check Nut Sizes: Welded on the top. Checknut will have the threadings of 1" BSPT, 1.25" BSPT, 1.5" BSPT, 2" BSPT or 2.5" BSPT.

- Length - 8" to 72'
- Tube Dia - 3/8" to 5/8"
- Volts - 250 - 440V
- Watts - 500 to 60.0 KW



CORPORATE

115, Jaywant Ind. Estate, Opp. Sobo Central Mall,
63, Pt. M. M. Malaviya Road, Mumbai 400 034, India
Tel: +91 22 2353 1025; Fax: +91 22 2351 7431
Mob: +91 93 2224 4540

Email: info@heatsource.in

FACTORY

Bldg No. E-8, Parasnath Complex, Village Valgaon,
Dapoda Road, Tal. Bhiwandi, Thane 421 302, India
Tel: +91 2522 645665; Mob: +91 93222 32090
Mob: +91 98207 12343

Web: www.heatsource.in